



PROPOSAL

Especially Prepared For:

**MIKE GARAND
TOWN OF EAST MONTPELIER
P/O BOX 157
EAST MONTPELIER, VT 05651**

Presented By:

**Gary Barrows
Sheldon Trucks
137 Avenue A**

Williston, Vermont 05495



CHASSIS SPECIFICATIONS SUMMARY

February 01, 2016

2017 MACK GU713

 SNOW PLOW. On/Off Hwy
 STRAIGHT TRUCK WITHOUT TRAILER

Engine	MACK MP8-425M 425HP	Transmission	4500-RDS-6
		Clutch	OMIT CLUTCH
Front Axle	18,000# FXL18	Rear Axle	46,000# RT46-164EH Ratio 5.63
Suspension	18,000#	Suspension	46,000# CHALMERS
Tires	Front: 315/80R22.5 Rear: 12R22.5	Wheels	22.5x9.0 ALUMINUM DISC 22.5x8.25 ALUMINUM DISC
Ratings	GVW: 64,000# GCW: 80,000#	Fuel Tanks	LH: 72gal
Fifth Wheel		Sleeper	

PRICING SUMMARY

	<u>List Price</u>
CHASSIS BASE	\$201,757.00
Factory Options	\$34,612.00
Allison Pricing	\$10,440.00
Freight	\$2,100.00
Less Additional Factory Rebate	
Sales Allowances	
TOTAL FACTORY	\$248,909.00
Locally Installed Options	\$750.00
Soft Products/Bulldog Protection Plans	\$0.00
TOTAL FACTORY & LOCAL	\$249,659.00
Less Customer Discount from List	\$120,362.06
SELLING PRICE (Excluding Taxes/Fees/Trade)	\$129,296.94
Less Trade Allowances per New Vehicle	\$43,000.00
QUOTED PRICE OR TRADE DIFFERENCE	\$86,296.94
Surcharge	\$0.00
Net FRET or Canadian GST Taxes	\$0.00
Tire Tax Credit (Municipal Only)	(\$416.94)
Sales/Usage Taxes	\$0.00
License/Title/Etc.	
Misc Fees not subject to FRET	
ACQUISITION COST (Include Trade if applies)	\$85,880.00
Less Down Payment	
BALANCE DUE Per Unit	\$85,880.00
PRICE (Total Order)	\$85,880.00
BALANCE DUE (Total Order)	\$85,880.00


TRADE: 2008 INTERNATIONAL 7600 Vin#1HTWYSBT08JO45289
 WITH BODY/PLOW & WING. TRADE CONDITIONS: TIRES AND
 BRAKES TO BE AT LEAST 50%, ALL EQUIPMENT TO BE FULLY
 OPERATIONAL AND BE VT. STATE INSPECTABLE

Total Quantity: 1

Estimated Total Weight: 18,157#

Reference#: AIIB015717A

X
 Prepared For: _____ Customer Signature _____ Date _____
 TOWN OF EAST MONTPELIER
 P/O BOX 157
 EAST MONTPELIER, VT 05651
 Phone: 802-223-5870
 Fax -

Presented By:  2/1/2016
 Dealer Signature _____ Date _____
 Gary Barrows
 Sheldon Trucks
 137 Avenue A
 Williston, Vermont 05495
 802 658 3314

Prepared For:

TOWN OF EAST MONTPELIER
P/O BOX 157
EAST MONTPELIER, VT 05651
(802) 223-5870

Presented By:

Sheldon Trucks
137 Avenue A
Williston, Vermont 05495
802 658 3314

Page 1

Feb 1, 2016
2017 GU713
Ref#: AIIB015717A

Description**ORDER/CUSTOMER/VEHICLE INFORMATION**

INITIAL REGISTRATION LOCATION, UNITED STATES, VERMONT

LANGUAGE, ENGLISH

IDLE EMISSION CERTIFICATION, IDLE EMISSION CERTIFICATION - CARB 08

TYPE OF SERVICE, MUNICIPAL

VEHICLE APPLICATION CLASS, HEAVY VOCATIONAL - Unlimited operation on concrete, asphalt, or maintained gravel/packed dirt with a maximum 3% grade; limited operation on unmaintained surfaces with maximum 5% grade; limited operation on concrete, asphalt, or maintained gravel/packed dirt with maximum 10% grade. (3 AXLES) 78,000 lbs (35,281 kg) MAX GVW. (4 AXLES) 80,000 lbs (36,288 kg) MAX GVW.

CARRIER APPLICATION, NOT AVAILABLE

VEHICLE TYPE, STRAIGHT TRUCK WITHOUT TRAILER

VEHICLE USE AND BODY/TRAILER TYPE, SNOW PLOW. On/Off Hwy

BRAKE - STOPPING DISTANCE, BRAKE REGULATION, STOPPING DISTANCE 94M (310FT)

FILE STATUS, QUOTE

PRICE BOOK LEVEL, 2017A PRICE BOOK LEVEL

PRODUCT CLASS, PRODUCT CLASS 28

OPERATING CONDITIONS

TOPOGRAPHY, GRADES <3% GREATER THAN 98% OF DRIVING DISTANCE MAX GRADE 8%

TRANSPORTATION CYCLE, VOCATIONAL

ROAD CONDITION, WELL MAINTAINED SURFACED ROADS >95% DRIVING DISTANCE

AMBIENT TEMPERATURE UPPER LIMIT, AMBIENT TEMPERATURE HOT. WARMER THAN 104 F (40 C) ALLOWED UP TO 25 HOURS PER YEAR

BVS/FRT AXLE POS/SALES PACKAGES

CHASSIS (BASE MODEL), GU703 6-WHEEL TRUCK

CHASSIS PACKAGING SOLUTIONS, CLEAR BOC PACKAGE 7A INCLUDES: HHF Emission, B Box LH Rail, Air Tank(s)

Under B Box - remaining on rail, Cab Mounted Exhaust REQUIRES: 72 Gallon LH Sleeved Fuel Tank, Omit RH Tank,
WITHOUT FRONT AXLE SPACING

ENGINE/TRANSMISSION/CLUTCH

ENGINE, MACK MP8-425M 425 HP @1500-1800 RPM (PEAK) 1640 LB FT. MAX TORQUE @ 1100-1400 RPM

TRANSMISSION, 8 SPEED AUTOMATIC, ALLISON 4500-RDS-6 (4.70/0.67) RUGGED DUTY SERIES GEN 5 INCLUDES

TRANSMISSION COOLER, EXTERNAL OIL COOLER, INTERNAL FILTER, AND OIL LEVEL SENSOR

CLUTCH, OMIT CLUTCH

EXHAUST/EMISSIONS

DPF, CLEARTECH HHF, DPF & SCR FRAME MTD, BOTH RH SIDE UNDER CAB

EXHAUST AFTER-TREATMENT SYSTEM, EXHAUST AFTER-TREATMENT SYSTEM DIESEL PARTIC FILTER CERAMIC
PASSIVE REGEN

EXHAUST, EXHAUST - CLEAR BOC, SINGLE (R/S) VERT EXHAUST CAB MOUNTED, LOWER VENTURI DIFFUSER, TURNED
END

SINGLE, BRIGHT FINISH HEAT SHIELD AND SCR COVER

FURNISH STEEL PAINTED HEAT SHIELD FOR FRAME MTD MACK CAP DPF

ENGINE EQUIPMENT

AIR COMPRESSOR, MERITOR/WABCO 318 18.7 CFM

INSIDE/OUTSIDE AIR INTAKE W/IN-CAB CONTROL FOR SNOWPLOWS

ALTERNATOR, DELCO 12V 160A (246) BRUSH-TYPE

Description

BATTERIES, (3) MACK 12V M/F GROUP 31 650/1950 CCA THREADED STUD TYPE W/KALAS CABLES

BUG SCREEN, RADIATOR MOUNTED

TO -34 DEGREES F (-37 DEGREES C)

MACK COOLANT CONDITIONER

ENGINE BRAKE, MACK ENGINE BRAKE POWER LEASH FOR MP8

ENGINE BLOCK HEATER, 120V 1500 WATT ENGINE BLOCK HEATER

FAN DRIVE, BEHR FAN AND ELECTRONIC MODULATING FAN DRIVE

FUEL-WATER SEPARATOR, MACK W/MANUAL DRAIN VALVE (INTEGRAL W/PRIMARY FUEL FILTER)

HOSES - RADIATOR/HEATER, SILICONE

OIL PAN, CORROSION RESISTANT OIL PAN

OIL PAN HEATER, W/O OIL PAN HEATER

ELECTRIC PREHEATER

STARTER, 12 VOLT DELCO MTHD 39

TETHER DEVICE, W/O TETHER DEVICE

TRANSMISSION EQUIPMENT/DRIVELINES

CLUTCH ASSIST (AIR), Information is not required

CLUTCH PEDAL, W/O CLUTCH PEDAL

mDRIVE - PARKER PUMP, W/O PARKER PUMP

TRANSMISSION SHIFT SETTINGS, W/O TRANSMISSION SHIFT SETTINGS

TRANSMISSION PTO1 SPLITTER RANGE, W/O PTO1 FOR SPLITTER RANGE

TRANSMISSION PTO2 SPLITTER RANGE, W/O PTO2 SPLITTER RANGE

TRANSMISSION BELL HOUSING, ALUMINUM

W/O TRANSMISSION DUSTPROOFING

FURNISH FOR ALLISON TRANSMISSION W/DIRECT MOUNT COOLER

SYNTHETIC LUBRICANT - TRANSMISSION, TRANSYND SYNTHETIC LUBE FOR ALLISON TRANS

VOCATIONAL PACKAGE - ALLISON, ALLISON GEN 5 PACKAGE #223, ON/OFF HWY, SHIFT TO NEUTRAL W/PARKING

BRAKE ENGAGED

WITHOUT DRIVESHAFT GUARD FOR CENTER BEARING

DRIVELINE - MAIN, MERITOR 18 MXL "XTENDED LUBE"

DRIVELINE - INTERAXLE, MERITOR 17 MXL "XTENDED LUBE"

CAB (A thru G)

MACK (BERGSTROM) INTEGRAL W/HEATER COMBINATION HEATER/DEFROSTER AND CONDITIONER

AIR RESTRICTION MONITOR (INTAKE), AIR RESTRICTION MONITOR (DISPLAYED IN CO-PILOT)

DASH CONTROL/POWER SUPPLY/LOCAL INSTALLATION PLOW LAMPS W/LEAD FURNISH AT GRILLE W/2W/3W

WEATHER PACK CONNECTION

CAB CONFIGURATIONS, LH-DRIVE CA68 CONV CAB

WITHOUT CAB CLEANOUT

CAB MOUNTING, AIR SUSPENSION

CERTIFIED WEIGHT

PROVIDE (8) MISC SWITCHES (2) 15A IGN, (1) 20A IGN, (1) 10A IGN, (1) 15A BAT, AND (1) 20A BAT.

PARK BRAKE AND ENGINE RUNNING ACTIVATED

(4) DOME LAMPS - DOOR AND SWITCH ACTIVATED

FENDER EXTENSIONS, FENDER EXTENSIONS

5LB (ABC RATED/AMEREX) MOUNTED BETWEEN LH SEAT BASE AND DOOR WITH VALVE AIMED REARWARD

GAUGE CLUSTER, EXHAUST PYROMETER AND TRANSMISSION OIL TEMPERATURE GAUGES

GAUGES, ENGLISH/METRIC DISPLAY

TOWN OF EAST MONTPELIER

Ref#: AIB015717A

Page 3

Description

WITHOUT REAR AXLE OIL TEMPERATURE GAUGE
 W/O INSIDE/OUTSIDE TEMP GAUGE OPTION
 GEAR SHIFT, DASH MOUNTED SHIFTER
 GLASS - CAB WINDOW, HEATED TINTED WINDSHIELD ONLY, TINTED SIDE AND REAR WINDOW
 BRIGHT FINISH EXTERIOR CAB GRAB HANDLES, BLACK FINISH GRAB HANDLE RH INTERIOR WINDSHIELD POST
 GRILLE - HOOD AIR INTAKE, GRILLE PAINTED GRAY
 GRILLE, BRIGHT FINISH GRILLE W/O SURROUND RADIATOR MOUNTED

CAB (H thru R)

HEADLINER, VINYL COVERED FOAM PADDED HEADLINER
 HOOD AND FENDERS, COMPOSITE MATERIAL - TILTABLE W/INSPECTION HATCH
 PAINTED HOOD LATCHES
 HORN - AIR, (1) MACK RECTANGULAR SINGLE TRUMPET
 HORN - ELECTRIC, SINGLE TONE
 IDENTIFICATION/CLEARANCE LIGHTS, (5) MARKER AND CLEARANCE, INCANDESCENT, SURFACE MOUNTED
 IN-DASH STORAGE, W/O UPPER STORAGE OPTION
 INSTRUMENT CLUSTER DISPLAY, CO-PILOT DRIVER DISPLAY, ENHANCED 4.5" DIAGONAL LCD DISPLAY W/4-BUTTON
 STALK CONTROL W/O DIAG DISPLAY
 INSTRUMENT PANEL, WOODGRAIN FINISH
 INTERIOR TRIM (PEDIGREE - SANDSTONE) Vinyl headliner, cloth/vinyl seat trim, 2 netted storage compartments and center CB
 radio mounting provisions in overhead console, rear panel with storage pouch, signature polyurethane floor mat, brushed nickel
 instrument panel with chrome gauge bezels, diamond pattern fabric on doors, padded interior sun visors both sides, 2 spoke
 urethane grip brushed nickel spokes, brushed nickel Mack horn cap, adjustable tilt/telescoping steering column, hand crank lhr/rh
 windows, 2 general overhead lights, 1 driver overhead light & 1 map non-glare overhead light, 2 12V power sources, 2 cup
 holders, 2 trash bag hooks, 2 coat hangers, rh storage compartment, seat belt retractors, rh door peep window, lighted door
 mounted map pocket lights.

CHASSIS KEYED AT RANDOM - 2 KEYS

MIRRORS - EXTERIOR, WEST COAST, RH & LH BRIGHT FINISH MACK BULLDOG HEATED

MIRRORS - CONVEX TYPE, BRIGHT FINISH, LH & RH 8.0" DIA HEATED; MOUNTED BELOW LOWER ARM OF WEST COAST
 MIRROR

OVERHEAD CONSOLE, (2) STORAGE COMPARTMENTS AND NET RETAINERS W/CENTER MOUNTING FOR CB
 PROVISIONS

AM/FM PREMIUM STEREO, CD-PLAYER, MP3, WEATHERBAND, HANDSFREE INTERFACE, BLUETOOTH

RADIO ANTENNA, CAB MOUNTED BEHIND LH DOOR

RADIO ANTENNA - CB, PREP KIT FOR MOUNTING ON LT SIDE MIRROR (W/O ANTENNA)

CB RADIO MOUNTING REINFORCEMENT IN HEADER CONSOLE

REFLECTOR KIT, EMERGENCY TRIANGLE KIT PARALLEL TO INSIDE SURFACE OF RIDERS SEAT BASE

CAB (S thru Z)

SEAT - DRIVER, AIR- NATIONAL 2000 (HI-BACK) SINGLE CHAMBER AIR LUMBAR, 2 POSITION FRONT CUSHION ADJ.

SEAT - RIDER, MACK FIXED (MID-BACK) NON-SUSPENSION

SEAT ARM RESTS, INBOARD MOUNTED ARM REST, DRIVER'S SEAT ONLY

SEAT COVERING, CLOTH W/VINYL TRIM DRIVER AND RIDER

SEAT BELTS/RETRACTORS, LAP AND SHOULDER W/CAB MOUNTED SHOULDER BELT W/ADJUSTABLE D-RING FOR
 DRIVER & RIDER SEATS

W/O ROOF VENT VENTILATION

STEERING COLUMN, ADJUSTABLE TILT TELESCOPE

STEERING WHEEL, TWO SPOKE URETHANE GRIP BRUSHED NICKEL SPOKES

Description**STORAGE POUCH REAR**

SUN VISOR - INTERIOR, BOTH SIDES (PADDED VINYL)

TURN SIGNAL SWITCH, SELF CANCELLING TURN SIGNALS

WINDOW CONTROLS, POWER WINDOW LIFT WITH ELECTRIC DOOR LOCK, LH & RH

WINDSHIELD, 2-PIECE WINDSHIELD

WINDSHIELD WASHER RESERVOIR, WINDSHIELD WASHER RESERVOIR INSTALLED BOC

WINDSHIELD WIPERS, 2 SPEED ELECTRIC MOTOR W/INTERMITTENT FEATURE

FRAME EQUIPMENT/FUEL TANKS

BUMPER - FRONT, EXT.-SWEPT BACK-STEEL CHANNEL 122.5"/3112 mm BBC

CROSSMEMBERS, BOC AND INTERMEDIATE(S) STEEL MD BACK-TO-BACK CHANNEL

CROSSMEMBER (BEHIND REAR AXLE), W/O OPTIONAL CROSSMEMBERS BEHIND REAR AXLE/BOGIE

WITHOUT FIFTH WHEEL MOUNTING ANGLES

FRONT FRAME EXTENSION, 20" FOR SNOW PLOW MOUNT (CONT' PARENT RAIL) W/TILT W/INSPECTION HATCH TYPE

HOOD W/SWEPT-BACK STEEL BUMPER

TOWING DEVICE - FRONT, HOOKS

TOWING DEVICE - REAR, HOOKS (FRAME MOUNTED)

FUEL TANK - LH, 72 GALLON (276 L) ALUMINUM 28" DIAMETER

FUEL TANK - RH, OMIT RH STANDARD

FUEL TANKS - BRIGHT FINISH, W/O SPECIAL FINISH FUEL TANK

STANDARD FINISH STEPS AND STAINLESS STEEL BRIGHT FINISH STRAPS

8.7 GALLON (33 L) DEF TANK

WITHOUT DEF TANK COVER

W/O FUEL LINE OPTION

FURNISH STANDARD FUEL TANK CAP

W/O ISOLATED TANK(S)

RELOCATE FUEL TANK, W/O RELOCATED FUEL TANK(S)

FRONT AXLE/EQUIPMENT/TIRES

FRONT AXLE, 18000# (8165kg) MACK FXL18 (WIDE PIVOT CENTER) STRAIGHT SPINDLE/UNITIZED BEARINGS

FRONT AXLE - TWIN STEER, WITH SINGLE STEER FRONT AXLE

TIRES BRAND/TYPE - FRONT, BRIDGESTONE - TUBELESS RADIAL PLY, (2) 315/80R22.5 20 L M860A (ALL POS)

WHEELS - FRONT, ALUMINUM DISC

(2) 22.5x9.0 ALCOA LVL ONE, 10-HOLE HUB PILOTTED (11 1/4"/280mm BC) 5.98" INSET, #89465X

WHEELS - POLISHED (FRONT), MACHINE CLEAN BUFFED-ALL WHEELS

BRAKES - FRONT, MERITOR "S" CAM TYPE 16.5" x 6" Q+

BRAKE DRUMS - FRONT, CAST OUTBOARD MOUNTED

DUST SHIELDS - FRONT BRAKE, FURNISH

HUBS - FRONT, FERROUS

FAG SCHAEFFLER, FRONT GREASE SEAL

SHOCK ABSORBERS, FRONT

SLACK ADJUSTERS - FRONT, HALDEX - AUTOMATIC

SPRINGS - FRONT, MACK MULTILEAF HD 18000# (8165kg) GROUND LOAD RATING

SPRING BUILD-UP, RH BUILD-UP FOR WING PLOW APPLICATIONS

STEERING, SHEPPARD SD110

REAR AXLE/EQUIPMENT/TIRES/RATIOS

REAR AXLE/SUSPENSION, 46000# (20900kg) MERITOR RT46-164EH, RT46-164EH WITH CHALMERS 46000# L HIGH

STABILITY W/#29 CAN

Description

4S/4M SYSTEM REAR WHEEL END SENSORS

W/O WIDE TRACK AXLE OPTION

TIRES BRAND/TYPE - REAR, BRIDGESTONE - TUBELESS RADIAL PLY, (8) 12R22.5 16 H M843 (ALL POSITION)

CARRIER/RATIO - REAR AXLE, MALLEABLE HOUSING, 5.63 RATIO

WHEELS - REAR, ALUMINUM DISC

(8) 22.5x8.26 (210 mm) ALCOA LVL ONE 10-HOLE HUB PILOTED (11 1/4" 286mm BOLT CIRCLE)

WHEELS - POLISHED (REAR), MACHINE CLEAN BUFFED - ALL WHEELS

BRAKES - REAR, MERITOR "S" CAM 16.5"x7" Q+

BRAKE DRUMS - REAR, CAST OUTBOARD MOUNTED

DUST SHIELDS - REAR BRAKE, FURNISH

HUBS - REAR, CONMET IRON PRESET REAR HUB W/INTEGRATED SPINDLE NUT

PREMIUM HUB OIL REAR SEAL

POWER DIVIDER LOCKOUT W/WARNING LIGHT AND BUZZER (INCLUDES IN CAB MANUAL AIR VALVE)

SHOCK ABSORBERS - (4), OUTBOARD MOUNTED ON FORWARD AND REAR AXLES EACH SIDE

W/O SHOCK INSULATORS

SLACK ADJUSTERS - REAR, HALDEX - AUTOMATIC

SUSPENSION - AXLE SPACING, 54" AXLE SPACING (BOGIE WHEELBASE)

SUSPENSION - HEIGHT CONTROL KIT, W/O AIR SUSPENSION HEIGHT CONTROL

AIR SUSPENSION DUMP WARNING, WITHOUT AIR SUSPENSION DUMP WARNING

SPRING BRAKE CHAMBERS - VENDOR, MGM MODEL TR-T (TAMPER RESISTANT)

REAR SPRING BRAKE CHAMBERS 30/30 TYPE

SYNTHETIC LUBRICANT - REAR AXLE, FACTORY OPTION LUBE REAR AXLE

TRANSVERSE TORQUE RODS (BOTH AXLES)

DRIVER CONTROLLED INTER WHEEL DIFFERENTIAL LOCK BOTH RR AXLES, MANUAL AIR VALVE W/WARNING LIGHT

W/O PROTECTIVE NYLON SPACER BETWEEN DISCS WHEEL TO DRUM

STANDARD WHEEL STUD OPTION

FRAME/WHEELBASE/PLATFORM

WHEELBASE, 208" (5296 mm) WB 121" CA (3072 mm)

PLATFORM, 183" LP (4652 mm) 62" AF (1590 mm) USED WITH 208" WB

FRAME RAILS, 11.811" x 3.54" x .44" (300 x 90 x 11.1mm) STEEL Section Modulus: 23.5 cu in/RBM 2,820,000 in lbs per rail

FRAME REINFORCEMENT - INSIDE, W/O 5MM INSIDE CHANNEL REINFORCEMENT

AIR/BRAKE

AIR DRYER, MERITOR/WABCO HEATED AIR DRYER, 1200 W/COALESCING OIL FILTER

W/O RELOCATED AIR TANKS

AIR RESERVOIRS, ALUMINUM, STANDARD FINISH

ANTI-LOCK BRAKE SYSTEM, BENDIX WITHOUT TRACTION CONTROL

AIR CONTROL VALVES - VENDOR, BENDIX SWITCHES AND VALVES WHERE POSSIBLE

BRAKE CONTROL VALVE SYSTEM, SINGLE VALVE SYSTEM

DRAIN VALVES, MANUAL DRAIN VALVES, WITH LANYARDS ON ALL TANKS

W/O HAND CONTROL VALVE

INCREASED AIR CAPACITY, W/O INCREASED AIR RESERVOIR CAPACITY

W/O TRAILER ACCESS PACKAGE

TRAILER CONNECTIONS

TRAILER AIR CONNECTIONS, OMIT TRAILER AIR BRAKE CONNECTIONS

WITHOUT HOSE TENDER

W/O TRAILER AIR HOSES

Description

W/O TRAILER ELECTRICAL CABLE

TRAILER ELECTRICAL RECEPTACLE, WITHOUT TRAILER ELECTRICAL RECEPTACLE

OMIT TRAILER CONNECTORS HOLDER

ELECTRICAL

BACK-UP ALARM, ECCO BACK-UP ALARM 575 CONSTANT SOUND LEVEL 107 db

BATTERY BOX COVERS, POLISHED ALUMINUM

BATTERY BOX - MOUNTING, (1) BATTERY BOX LEFT HAND RAIL

W/O OPTIONAL DASH MTD. LIGHT

CHASSIS & POWER HARNESS WITH HEAVY DUTY CASING

"BODY LINK" III W/O CAB PASS-THRU

REAR LIGHTING, FURNISH REAR LIGHTING

PAINT

PAINT - CAB EXTERIOR, SINGLE COLOR, MACK RED [PPG: P9189]

PAINT - CAB, URETHANE CLEAR COAT

PAINT - CHASSIS RUNNING GEAR, MACK BLACK (URETHANE)

PAINT - BUMPER, SAME AS CHASSIS RUNNING GEAR

PAINT - FRONT SPOKE WHEELS, WITHOUT OPTIONAL SPOKE WHEEL PAINT

WITHOUT OPTIONAL SPOKE WHEEL PAINT

WITHOUT SPECIAL PRE-FINISHED OPTION

WITHOUT SPECIAL PRE-FINISHED OPTIONS

PAINT PROCESS CODES

SAME COLOR AS CHASSIS RUNNING GEAR (5ZB-A1X)

CHASSIS RUNNING GEAR - STD COLOR (MACK BLACK) (6AB-Z1X)

W/O PAINT FOR FUEL TANK (7HB-Z1X)

W/O CUSTOM PAINT FOR HUB&DRUM/SPOKES (5YB-Z1X)

W/O CUSTOM PAINTED FRONT/REAR RIM/WHEEL (6BB-Z1X)

PTO/SPECIALTY/ADDITIONAL EQUIPMENT

PTO - CRANKSHAFT ADAPTER, 1350 SERIES FLANGE (DOES NOT INCLUDE FRONT FRAME EXTENSION)

PTO - REAR ENGINE (REPTO), WITHOUT REAR ENGINE POWER TAKE OFF

TORQUE CONVERTER TC541

W/O SPECIAL DECALS

V-MAC IV PROGRAMMABLE PARAMETERS

CUSTOMER VEHICLE LIMITING SPEED (MPH) 68 mph

PEDAL ROAD SPEED LIMITER (MPH) 68 mph

LGVLS FEATURE ACTIVATION Omit

LOWER GEAR VEHICLE LIMITING SPEED (MPH) 00 mph

SOFT RSL Omit

PDLO ENGAGED VLS FEATURE Furnish

PDLO ENGAGED VEHICLE LIMITING SPEED 25 rpm

CRUISE CONTROL SETTINGS WALLISON TRANS

CRUISE CONTROL MAX SET SPEED (MPH) 65 mph

CRUISE CONTROL MIN SET SPEED (MPH) 20 mph

CRUISE CONTROL AUTORESUME W/CLUTCH Omit

CRUISE'N BRAKE ENGAGEMENT DELAY (MPH) 3 mph

SMOOTH CRUISE Omit

ENGINE OVERSPEED COMPANY LIMIT (RPM) 2200 rpm

TOWN OF EAST MONTPELIER

Ref#: AIIB015717A

Page 7

Description

FUELED ENGINE OVERSPEED COMPANY LIMIT (RPM) 2100 rpm
 VEHICLE OVERSPEED COMPANY LIMIT (MPH) 75 mph
 FUELED VEHICLE OVERSPEED COMPANY LIMIT (MPH) 70 mph
 IDLE LOGGING DELAY (MIN) 2

Monthly Trip Summary

PERIODIC TRIP HOUR OF DAY 0 (disable)
 PERIODIC TRIP DAY OF WEEK 0 (disable)
 PERIODIC TRIP DAY OF MONTH 1

DAYTIME RUNNING LIGHTS W/O OVERRIDE SWITCH

DRL OVERRIDE SWITCH SPEED THRESHOLD (MPH) 00
 DRL OVERRIDE SWITCH OFF TIME (MIN) 00 mph
 CO-PILOT FLEET TRIP PROGRAMMING ACCESS Fleet Level
 FLEET MANAGEMENT VIA CO-PILOT Omit
 EHT MAX ENGINE SET SPEED (RPM)

2100 rpm

EHT MIN ENGINE SET SPEED (RPM) 700 rpm
 EHT VEHICLE SPEED RANGE LIMIT (MPH) 10 mph
 EHT RAMP RATE (RPM/Sec)
 EHT SINGLE SPEED CONTROL ACTIVATION Omit
 EHT SINGLE SPEED CONTROL SET SPEED (RPM) 0000 rpm
 EHT JUMP-TO-MIN SET SPEED Omit
 EHT HOLD TO NEAREST RPM 50 rpm
 EHT ACCEL-DECEL BUMP-UP RPM 50 rpm
 EHT ACCEL-DECEL BUMP-DOWN RPM 50 rpm
 ENGINE PROTECTION - OIL PRESSURE SHUTDOWN Furnish
 ENGINE PROTECTION - COOLANT LEVEL SHUTDOWN Omit
 ENGINE PROTECTION - COOLANT TEMP SHUTDOWN Furnish
 ENGINE PROTECTION - ENGINE OIL TEMP SHUTDOWN Furnish
 ENGINE PROTECTION TRANS OIL TEMP SHUTDOWN Furnish
 ALLOW FAN OVERRIDE WHEN PARKED Omit
 FAN ACTIVATION WITH PTO Omit

FUEL ECONOMY INCENTIVE FOR USE WITH INSTRUMENT CLUSTER DISPLAY (C0J 0002)

FEI PENALTY TARGET FUEL ECONOMY No Driver Incentive
 FEI PENALTY TARGET FUEL ECONOMY (MPG) 0.0
 FEI PENALTY VEHICLE SPEED DECREASE (MPH) 0 mph
 FEI REWARD TARGET FUEL ECONOMY (MPG) 0.0
 FEI REWARD VEHICLE SPEED INCREASE (MPH) 0 mph
 FEI DISTANCE CALCULATION INTERVAL (Miles) 00

GOVERNOR SETTINGS FOR USE WITH AUTOMATIC TRANSMISSIONS

GOVERNOR TYPE Min-Max Governor
 ENGINE HIGH IDLE SPEED IF STOPPED 0000
 VEHICLE ACCELERATION LIMITING FEATURE Disable
 REDUCED ENGINE RPM RANGE IN UPPER GEARS FEATURE Disable
 ENGINE RPM LIMIT IN UPPER GEARS 0000
 1st TRANS RATIO FOR REDUCED HIGH IDLE 0000
 LAST TRANS RATIO FOR FULL HIGH IDLE 0000

Description

ENGINE LOW IDLE SET SPEED (RPM) 650 rpm
 DRIVER LOW IDLE ADJUST FEATURE ACTIVATION Omit
 SMART IDLE FEATURE ACTIVATION Omit
 SMART IDLE ELEVATED IDLE RPM TIME (MINS) 10
 IDLE S/D ABS TAMPER CHECK Omit
 IDLE COOLDOWN FEATURE ACTIVATION Omit
 IDLE SHUTDOWN FEATURE ACTIVATION Omit
 IDLE SHUTDOWN TIME (MINS) 10
 IDLE SHUTDOWN WARNING TIME (SECS) 30
 IDLE SHUTDOWN WARM-UP TEMPERATURE (DEG F) 100
 IDLE SHUTDOWN WARM-UP TIMER (MINS) 5
 IDLE S/D OVERRIDE W/EHT Omit
 IDLE S/D OVERRIDE W/PTO Furnish
 IDLE S/D OVERRIDE W/ENGINE LOAD Omit
 IDLE S/D OVERRIDE % ENGINE LOAD THRESHOLD 20
 IDLE S/D CONTROL W/O Idle Shutdown
 IDLE S/D OVERRIDE LOWER TEMP. THRESHOLD (DEG F) 80
 IDLE S/D OVERRIDE UPPER TEMP. THRESHOLD (DEG F) 80
 MAINTENANCE MONITOR FEATURE ACTIVATION Furnish
 PTO 1 MAX ENGINE SET SPEED (RPM) 2100 rpm
 PTO 1 MIN ENGINE SET SPEED (RPM) 600 rpm
 PTO 1 VEHICLE SPEED RANGE LIMIT (MPH) 10 mph
 PTO 1 RAMP RATE (RPM/Sec) 100
 PTO 1 SINGLE SPEED CONTROL ACTIVATION Omit
 PTO 1 SINGLE SPEED CONTROL SET SPEED (RPM) 1000 rpm
 PTO 1 SINGLE SPEED CONTROL AUTOSET Omit
 PTO 1 JUMP-TO-MIN SET SPEED Omit
 PTO 1 VEHICLE LIMITING SPEED (MPH) 60 mph
 PTO 1 HOLD TO NEAREST RPM 50 rpm
 PTO 1 ACCEL-DECEL BUMP-UP RPM 50 rpm
 PTO 1 ACCEL-DECEL BUMP-DOWN RPM 50 rpm
 PTO 2 MAX ENGINE SET SPEED (RPM) 2100 rpm
 PTO 2 MIN ENGINE SET SPEED (RPM) 600 rpm
 PTO 2 VEHICLE SPEED RANGE LIMIT (MPH) 10 mph
 PTO 2 RAMP RATE (RPM/Sec) 100
 PTO 2 SINGLE SPEED CONTROL ACTIVATION Omit
 PTO 2 SINGLE SPEED CONTROL SET SPEED (RPM) 1000 rpm
 PTO 2 SINGLE SPEED CONTROL AUTOSET Omit
 PTO 2 JUMP-TO-MIN SET SPEED Omit
 PTO 2 VEHICLE LIMITING SPEED (MPH) 60 mph
 PTO 2 HOLD TO NEAREST RPM 50 rpm
 PTO 2 ACCEL-DECEL BUMP-UP RPM 50 rpm
 PTO 2 ACCEL-DECEL BUMP-DOWN RPM 50 rpm
 SPEED SENSOR TAMPER DETECTION SYSTEM ACTIVATION Furnish
 SPEED SENSOR TAMPER DETECTION TORQUE LIMIT (%) 60

DEALER INFORMATION

Description

ENGINE WARRANTY, 2YR/250,000 MILES ENGINE WARRANTY US10
PILOT INSPECTION, WITHOUT PILOT INSPECTION
DEALER PREP
HOOD MOUNTED CONVEX MIRRORS
STANDARD SHIPPING INSTRUCTIONS
MARKETING PROMOTION, NO FMV LEASE, TRADE BACK RESIDUAL OR TRADE IN WITH MACK PARTICIPATION
SOFT PRODUCTS/BULLDOG PROTECTION
2 YEARS COVERAGE
NO PARTNERED SERVICES PROVIDED