
JASON COTE-WONG RESIDENTIAL SUBDIVISION AND STORMWATER PERMITTING

EAST MONTPELIER, VERMONT
JUNE 21, 2017



LOCATION PLAN

SCALE: 1" = 2000'

OWNER:

JASON COTE-WONG
4028 U.S ROUTE 2
EAST MONTPELIER, VERMONT 05651
(802) 223-7171

ENGINEER:



34 SCHOOL STREET LITTLETON, NH 03561 (603) 444-4111

SURVEYOR:

CHASE & CHASE SURVEYORS
301 NORTH MAIN ST., SUITE 1
BARRE, VERMONT 05641
(802) 479-9636

SHEET INDEX

SHEET 1 COVER SHEET
SHEET 2 EXISTING CONDITIONS

SHEET 3 PROPOSED SITE PLAN OVERVIEW
SHEET 4 PLAN AND PROFILE STA 0+00-9+00

SHEET 5 PLAN AND PROFILE STA 9+00 - 16+90

SHEET 6 PRE DRAINAGE AREA MAP WITH SOIL COLOR DELINEATION POST DRAINAGE AREA MAP WITH SOIL COLOR DELINEATION


SHEET 8 STORMWATER DETAILS AND NOTES

DATE OF PRINT


JUNE 28 2017


HORIZONS ENGINEERING






16202 Wong Stormwater/DWGS/Final/HE_S/TTEPLAN_4.dwg, SH3-PROPOSED COND, 6/28/2017 8:17:35 AM, M






TA16202 Wong Stormwater/DWGS/Final/HE_SITEPIAN_4/dwg. SH5-P&P, 6/28/2017 8:17:45 AM, MBurnell



T*:16202 Wong Stormwater\DWGS\Fina\\HE_SITEPIAN_4.dwg, SH6-PREDEV COLOR MAP, 6/7



\16202 Wong Stormwater\DWGS\Fina\HE_SITEPLAN_A dwg, SH7-POSTDEV COLOR MAP, 6/28/201

SEEDING RECOMMENDATIONS

1. GRADING AND SHAPING

A. SLOPES SHALL NOT BE STEEPER THAN 2:1; 3:1 SLOPES OR FLATTER ARE PREFERRED. WHERE MOWING WILL BE DONE, 3:1 SLOPES OR FLATTER ARE RECOMMENDED.

2. SEEDBED PREPARATION

A. SURFACE AND SEEPAGE WATER SHOULD BE DRAINED OR DIVERTED FROM THE SITE TO PREVENT DROWNING OR WINTER KILLING OF THE PLANTS.

B. STONES LARGER THAN 4 INCHES AND TRASH SHOULD BE REMOVED BECAUSE THEY INTERFERE WITH SEEDING AND FUTURE MAINTENANCE OF THE AREA. WHERE FEASIBLE, THE SOIL SHOULD BE TILLED TO A DEPTH OF ABOUT 4 INCHES TO PREPARE A SEEDBED AND MIX FERTILIZER AND LIME THOROUGHLY INTO THE SOIL. THE SEEDBED SHOULD BE LEFT IN A REASONABLY FIRM AND SMOOTH CONDITION. THE LAST TILLAGE OPERATION SHOULD BE PERFORMED ACROSS THE SLOPE WHEREVER PRACTICAL.

3. ESTABLISHING VEGETATION

A. LIME AND FERTILIZER SHOULD BE APPLIED PRIOR TO OR AT THE TIME OF SEEDING AND INCORPORATED INTO THE SOIL. KINDS AND AMOUNTS OF LIME AND FERTILIZER SHOULD BE BASED ON AN EVALUATION OF SOIL TESTS. WHEN A SOIL TEST IS NOT AVAILABLE, THE FOLLOWING MINIMUM AMOUNTS SHOULD BE APPLIED:

-AGRICULTURAL LIMESTONE, 2 TONS PER ACRE OR 100 LBS. PER 1,000 SQ. FT. -NITROGEN (N), 50 LBS., PER ACRE OR 1.1 LBS. PER 1,000 SQ. FT. -PHOSPHATE (P₂O₅), 100 LBS. PER ACRE OR 2.2 LBS. PER 1,000 SQ. FT. -POTASH (K₂0), 100 LBS. PER ACRE OR 2.2 LBS. PER 1,000 SQ. FT.

(NOTE: THIS IS THE EQUIVALENT OF 500 LBS. PER ACRE OF 10-20-20 FERTILIZER OR 1,000 LBS. PER ACRE OF

B. SEED SHOULD BE SPREAD UNIFORMLY BY THE METHOD MOST APPROPRIATE FOR THE SITE. METHODS INCLUDE BROADCASTING, DRILLING, AND HYDROSEEDING, WHERE BROADCASTING IS USED, COVER SEED WITH .25 INCH OF SOIL OR LESS, BY CULTIPACKING OR RAKING.

. SEEDING GUIDE:	1	ı			1
	SEEDING	SOIL TYPE			
	MIXTURE		WELL	MOD. WELL	POORLY
USE	(SEE 3D)	DROUGHTY	DRAINED	DRAINED	DRAINED
STEEP CUTS AND FILLS,	A	FAIR	GOOD	GOOD	FAIR
BORROW AND DISPOSAL AREAS	В	POOR	GOOD	FAIR	FAIR
	С	FAIR	EXCELLENT	EXCELLENT	POOR
WATERWAYS, EMERGENCY SPILL- WAYS, AND OTHER CHANNELS WITH FLOWING WATER	A	GOOD	GOOD	GOOD	FAIR
LIGHTLY USED PARKING LOTS, ODD	A	GOOD	GOOD	GOOD	FAIR
AREAS, UNUSED LANDS, AND LOW INTENSITY USE RECREATION SITES	В	GOOD	GOOD	FAIR	POOR

D. SEEDING RATES:

MIXTURE		POUNDS PER ACRE	POUNDS PER 1,000 SQ. FT.
A TALL RESCUE CREEPING RED FESCU REDTOP	E	20 20 2	0.45 0.45 0.05
TOTAL:		42	0.95
B TALL FESCUE CREEPING RED FESCU CROWN VETCH OR FLATPEA	E	15 10 15 OR 30	0.35 0.25 0.35 OR 0.75
TOTAL:		40 OR 55	0.95 OR 1.35
C TALL FESCUE FLATPEA		20 30	0.45 0.75
TOTAL:		50	1.20

E. WHEN SEEDED AREAS ARE MULCHED, PLANTINGS MAY BE MADE FROM EARLY SPRING TO SEPTEMBER 15. WHEN SEEDED AREAS ARE NOT MULCHED, PLANTINGS SHOULD BE MADE FROM EARLY SPRING TO MAY 20 OR FROM AUGUST 10 TO SEPTEMBER 1


F. TEMPORARY SEEDING RATES:

SPECIES	POUNDS PER ACRE	POUNDS PER 1,000 SQ. FT.	REMARKS
WINTER RYE	112	2.5	BEST FOR FALL SEEDING. SEED FROM AUGUST TO SEPTEMBER 5TH FOR BEST COVER. SEED TO A DEPTH OF 1 INCH.
OATS	80	2.0	BEST FOR SPRING SEEDING. SEED NO LATER THAN MAY 15TH FOR SUMMER PROTECTION. SEED TO A DEPTH OF 1 INCH.
ANNUAL RYEGRASS	40	1.0	GROWS QUICKLY, BUT IS OF SHORT DURATION. USE WHERE APPEARANCES ARE IMPORTANT. SEED EARLY SPRING AND/OR BETWEEN AUGUST 15TH AND SEPTEMBER 15TH. COVER SEED WITH NO MORE THAN 0.25 INCH OF SOIL.
PERENNIAL RYEGRASS	30	0.7	GOOD COVER WHICH IS LONGER LASTING THAN ANNUAL RYEGRASS. SEED BETWEEN APRIL 1ST AND JUNE 1ST AND/OR BETWEEN AUGUST 15TH AND SEPTEMBER 15TH. MULCHING WILL ALLOW SEEDING THROUGHOUT THE GROWING SEASON. SEED TO A DEPTH OF APPROXIMATELY 0.5 INCH.

- A. HAY, STRAW, OR OTHER MULCH, WHEN NEEDED, SHOULD BE APPLIED IMMEDIATELY AFTER SEEDING.
- B. MULCH WILL BE HELD IN PLACE USING APPROPRIATE TECHNIQUES FROM THE BEST MANAGEMENT PRACTICE FOR MULCHING.

5. MAINTENANCE TO ESTABLISH A STAND

- A. PLANTED AREAS SHOULD BE PROTECTED FROM DAMAGE BY FIRE, GRAZING, TRAFFIC, AND DENSE WEED
- B. FERTILIZATION NEEDS SHOULD BE DETERMINED BY ON SITE INSPECTIONS. SUPPLEMENTAL FERTILIZER IS USUALLY THE KEY TO FULLY COMPLETE THE ESTABLISHMENT OF THE STAND BECAUSE MOST PERENNIALS TAKE
- C. IN WATERWAYS, CHANNELS, OR SWALES WHERE UNIFORM FLOW CONDITIONS ARE ANTICIPATED, OCCASIONAL MOWING MAY BE NECESSARY TO CONTROL GROWTH OF WOODY VEGETATION.



NO SCALE SOURCE: USDA SOIL CONSERVATION SERVICE

LEVEL LIP SPREADER INSTALLATION

- 1. CONSTRUCT THE LEVEL SPREADER LIP ON A ZERO PERCENT GRADE TO INSURE UNIFORM SPREADING OF RUNOFF.
- 2. LEVEL SPREADER SHALL BE CONSTRUCTED ON UNDISTURBED SOIL AND NOT ON
- 3. AN EROSION STOP SHALL BE PLACED VERTICALLY A MINIMUM OF SIX INCHES DEEP IN A SLIT TRENCH ONE FOOT BACK OF THE LEVEL LIP AND PARALLEL TO THE LIP. THE EROSION STOP SHALL EXTEND THE ENTIRE LENGTH OF THE LEVEL LIP.
- 4. THE ENTIRE LEVEL LIP AREA SHALL BE PROTECTED BY PLACING TWO STRIPS OF JUTE OR EXCELSIOR MATTING ALONG THE LIP. EACH STRIP SHALL OVERLAP THE EROSION STOP BY AT LEAST SIX INCHES.
- 5. THE ENTRANCE CHANNEL TO THE LEVEL SPREADER SHALL NOT EXCEED A 1 PERCENT GRADE FOR AT LEAST 50 FEET BEFORE ENTERING INTO THE SPREADER.
- 6. THE FLOW FROM THE LEVEL SPREADER SHALL OUTLET ONTO STABILIZED AREAS. WATER SHOULD NOT RE-CONCENTRATE IMMEDIATELY BELOW THE SPREADER.
- 7. PERIODIC INSPECTION AND REQUIRED MAINTENANCE SHALL BE PERFORMED.

OF 6 INCHES

-EROSION STOP

─1'--

FIRST STRIP OF

LEVEL LIP OF —

SPREADER

PROTECTIVE

MATERIAL


8. PROTECTIVE MATERIAL AND EROSION STOP SHALL BE NORTH AMERICAN GREEN C125 EROSION CONTROL BLANKET OR APPROVED EQUAL.

> OVERLAP BOTH STRIPS OF PROTECTIVE MATERIAL OVER EROSION STOP A MINIMUM


> > SECOND STRIP OF PROTECTIVE MATERIAL

— 6' MINIMUM

LEVEL SPREADER DETAIL




STONE LINED DITCH DETAIL




GRASSED SWALE DETAIL

NOT TO SCALE




TYPICAL ROAD CROSS SECTION


NOT TO SCALE




STONE DRIP EDGE DETAIL NOT TO SCALE



- 1. CONSTRUCT ROCK CHECK DAMS WHERE INDICATED ON THE PLANS OR AS NECESSARY
- 2. CONSTRUCT SPILLWAY IN CENTER OF ROCK CHECK DAM 6" BELOW TOP OF CHANNEL.
- 3. THE MAXIMUM SPACING BETWEEN THE CHECK DAMS SHOULD BE SUCH THAT THE TOE OF THE UPSTREAM CHECK DAM IS AT THE SAME ELEVATION AS THE SPILLWAY ELEVATION OF THE DOWNSTREAM CHECK DAM, THIS WILL VARY DEPENDING ON THE
- 4. ROCK CHECK DAMS SHALL CONSIST OF A WELL GRADED MIXTURE OF 2" 3" STONE.
- 5. REMOVE ROCK CHECK DAMS AND ANY ACCUMULATED SILT IN CHANNEL ONCE PERMANENT CHANNEL LININGS HAVE BEEN ESTABLISHED AND STABILIZED.



ROCK CHECK DAM DETAIL




TYPICAL CULVERT TRENCH DETAIL

NOT TO SCALE

DATE OF PRINT JUNE 28 2017 HORIZONS ENGINEERING

horizens Engineering All rights reserved



Littleton NH • New London NH • Newport VT

603-444-4111 603-877-0116 802-334-6434